

General

- Robust and reliable ultra slim scratch resistant housing
- Compatible with all SESA DMS
- NTCIP and NEMA TS4 compliant
- 19" rack – Light weight

Unique features:

- Web based firmware
- Full color touch screen interface
- Embedded digital I/Os
- Can communicate with several DMS simultaneously

Front Panel and Indicators

- Front panel:
 - Full Color Touch screen
 - Display graphics and sign status
- Power and reset switches
- Power, heartbeat, battery and communication indicators
- Digital I/Os status indicators
- Reset push button

Diagnostics and maintenance

- Real time monitoring of all DMS functionalities (display, temperature, humidity, power, etc...)
- Web based software to allow configuration and diagnostic

Communication Interfaces

- Two RS232 (DB-9)
- Two Ethernet 10/100 Base-T (RJ11)
- Two RS485 (DB-25)
- Supports all communication (fiber-optic, dial-up, cellular, radio, etc...)

Environment and Power

- -34 to +165 F (-37 to +74 C)
- Power: 12 – 24V DC
- Max Power consumption: 20W

Messaging

- Capable of any text and graphics
- Store up to 500 messages and 30 fonts
- Select pre-defined messages
- Activate messages by dry contacts with no additional hardware.

Dimensions

- 19" x 4 1/4" x 2"

NTCIP Compliance Table:

NTCIP 1101, NTCIP 1102, NTCIP 1103; NTCIP 1201, NTCIP 1203, NTCIP 2001, NTCIP 2103, 2201, NTCIP 2202, NTCIP 2301, NTCIP 8004.



Related products:

1. Controller Web Server
2. Light Controller SCU3
3. Messenger 6000 DMS
4. Messenger 5000 Task Specific DMS



SESA America, Inc
410 Harris Road, Smithfield RI02917
401.232.3370 www.sesamerica.com

Note: SESA policy is to constantly improve its product, all product descriptions are subject to change without notice.