

Wrong Way Sign / Front Access

General

- Blank Out Sign
- White Led
- Access Type: Front
- Text: WRONG WAY – 18"
- MUTCD compliant

Construction

- 5052 aluminum alloy
- NEMA 3R
- Structural: AASHTO D1.2-120 mph

Dimensions

- Height: 36" (914.4 mm)
- Length: 48" (1219.2 mm)
- Depth: 7" (177.8 mm)
- Weight: 35 Lbs (16 Kg)

Electrical Requirements

- 24 VDC – Solar Power available
- Typical Power (Amps): 9
- Max Power (Amps): 18

Environmental

- Operating Temperature: -30°F to +165°F (-34°C to +74°C)
- Storage Temperature: -40°F to +185°F (-40°C to +85°C)
- Humidity: 0% to 99% non-condensing

Standards

NEMA: All TS4 requirements met or exceeded including:

- Section 2 Environmental Requirements
- Mechanical construction
- Controller to sign interface
- Display properties
- DMS controller cabinet
- Electronics and electrical
- Performance monitoring
- Power requirements

Optical Performance

- White LED
- Viewing Angle: 30°
- Luminance: 16,100 cd/m²
- Contrast Ratio: 15:1

OPERATING MODES

Single Stroke

Double Stroke

Flashing

Steady



Note: SESA policy is to constantly improve its product, all product descriptions are subject to change



SES America, Inc
410 Harris Road, Smithfield RI02917
401.232.3370 www.sesamerica.com